

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: SR GREENPOXY 33

Product code: 2052. **EPOXY RESIN**

UFI: TRJ5-G0RY-3003-2UFC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: resin

Uses advised against : data not available

1.3. Details of the supplier of the safety data sheet

Registered company name: SICOMIN Composites.

Address: 31 avenue de la Lardiere - BP 23.13161. Chateauneuf les Martigues. France.

Telephone: +33 (0)4 42 42 30 20. Fax: +33 (0)4 42 81 29 29.

composites@sicomin.com Site web: http://www.sicomin.com

AUSTRALIAN Importer: Lavender CE Pty Ltd - 108 Westgate Street - Wacol, Qld, 4076 AUSTRALIA / M: 0409 892 032 / Ph: +61 7 3255 6924 /

Fax: +61 7 3255 6923 / Web: www.lavender-ce.com / Email: sheading@lavender-ce.com

1.4. Emergency telephone number: .

Association/Organisation: INRS / ORFILA tél: +33(0)1.45.42.59.59 - (FRANCE).

Other emergency numbers

Health and Safety Executive (HSE) Chemicals Regulation Directorate - Telephone: +44 151 951 3317 - USA: +1/800/424.9300 -

AUSTRALIA: Emergency Poison Advice: 131 126

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:







GHS05

GHS07

Signal Word: **DANGER**

Product identifiers:

EC 216-823-5 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE

BUTANEDIOLDIGLYCIDYL ETHER EC 219-371-7

Additional labeling:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Hazard statements:

SR GREENPOXY 33 - 2052

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/

...

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of water/...

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European

 $CHemicals\ Agency\ (ECHA)\ under\ article\ 57\ of\ REACH:\ http://echa.europa.eu/fr/candidate-list-table$

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

| Identification | (EC) 1272/2008 | Note | % |
|---------------------------------|-------------------------|------|---------------|
| CAS: 1675-54-3 | GHS07, GHS09 | | 80 <= x% < 90 |
| EC: 216-823-5 | Wng | | |
| REACH: 01-2119456619-26-XXXX | Skin Irrit. 2, H315 | | |
| | Skin Sens. 1, H317 | | |
| 2,2'-[(1-METHYLETHYLIDENE)BIS(4 | Eye Irrit. 2, H319 | | |
| ,1-PHENYLENEOXYMETHYLENE)]BISOX | Aquatic Chronic 2, H411 | | |
| IRANE | | | |
| CAS: 2425-79-8 | GHS07, GHS05 | | 20 <= x% < 23 |
| EC: 219-371-7 | Dgr | | |
| REACH: 01-2119494060-45-XXXX | Acute Tox. 4, H312 | | |
| | Skin Irrit. 2, H315 | | |
| BUTANEDIOLDIGLYCIDYL ETHER | Skin Sens. 1A, H317 | | |
| | Eye Dam. 1, H318 | | |
| | Acute Tox. 4, H332 | | |
| | | | |

Specific concentration limits:

| Identification | Specific concentration limits | ATE |
|---|-------------------------------|------------------------------|
| CAS: 1675-54-3 | Skin Irrit. 2: H315 >=5% | dermal: ATE = 2000 mg/kg BW |
| EC: 216-823-5 | Eye Irrit. 2: H319 C>= 5% | oral: ATE = 11400 mg/kg BW |
| REACH: 01-2119456619-26-XXXX | | |
| 2,2'-[(1-METHYLETHYLIDENE)BIS(4 ,1-PHENYLENEOXYMETHYLENE)]BISOX IRANE | | |
| CAS: 2425-79-8 | | inhalation: ATE = 10 mg/l 4h |
| EC: 219-371-7 | | (vapours) |
| REACH: 01-2119494060-45-XXXX | | dermal: ATE = 1130 mg/kg BW |
| | | oral: ATE = 1134 mg/kg BW |
| BUTANEDIOLDIGLYCIDYL ETHER | | |

Information on ingredients:

(Full text of H-phrases: see section 16)

SECTION 4: FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

If inhaled, move the patient to fresh air and keep warm and rest.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor:

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to remain under medical supervision for 48 hours.

SECTION 5: FIREFIGHTING MEASURES

Non-flammable

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- dry chemical agents
- carbon dioxide (CO2)
- foam

Unsuitable methods of extinction

In the event of a fire, do not use:

- water iet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode.

Wear conform with the European standard EN 469.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention:

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture at all times.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Store in original container protected from direct sunlight in a dry, cool and well ventilated area away from heat sources.

Keep container tightly closed in a dry place.

Store away from heat and cold.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

Scope advised: Stratification

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Final use:Workers.

Exposure method:

Dermal contact.

Potential health effects: Short term systemic effects.

DNEL: 8.3 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 8.3 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term systemic effects.

DNEL: 12.3 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 12.3 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Short term systemic effects.

DNEL: 0.75 mg/kg body weight/day

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 0.75 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Short term systemic effects.

DNEL: 3.6 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 3.6 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term systemic effects.

DNEL: 0.75 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 0.75 mg of substance/m3

Predicted no effect concentration (PNEC):

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Environmental compartment: Soil.
PNEC: 0.065 mg/kg

Environmental compartment: Fresh water. PNEC: 6 μg/l

Environmental compartment: Sea water. PNEC: 1 µg/l

Environmental compartment: Intermittent waste water.

PNEC: 0.013 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 0.341 mg/kg

Environmental compartment: Marine sediment. PNEC: 0.034 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 10 mg/l

8.2. Exposure controls

Use only with adequate ventilation or provided with ventilation at the source.

Personal protection measures, such as personal protective equipment









Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Physical state

Odour threshold:

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

Attention! If the protection group is insufficient.

Mask with filter type A, B, E, K, P

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| Physical state : | Viscous liquid. | |
|------------------|---------------------------|--|
| Colour | | |
| Color: | colorless to light yellow | |
| Odour | | |

| Melting point | <u> </u> |
|-------------------------------|---------------|
| Melting point/melting range : | Not relevant. |

Not stated.

| Freezing point | |
|-----------------------------------|-------------|
| Freezing point / Freezing range : | Not stated. |

| Boiling point or initial boiling point ar | nd boiling range | | |
|---|------------------|---------------|--|
| Boiling point/boiling range : | | Not relevant. | |

| | 110110101010 |
|---------------------------------|--------------|
| Flammability | |
| Flammability (solid, gas) : | Not stated. |
| Lower and upper explosion limit | |

| Explosive properties, upper explosivity limit (%): Not stated. | |
|---|--|
| Explosive properties, upper explosivity limit (%): | |

| Flash point | |
|---------------------------|-------------|
| Flash Point Interval : | FP > 100°C. |
| Auto-ignition temperature | |

| Self-ignition temperature : | Not relevant. |
|---|---------------|
| Decomposition temperature | |
| Decomposition point/decomposition range : | Not relevant. |

| рН | | |
|------------------------|---------------|--|
| pH (aqueous solution): | Not stated. | |
| pH: | Not relevant. | |

| pH (aqueous solution): | Not stated. |
|------------------------|--------------------------|
| pH: | Not relevant. |
| Kinematic viscosity | |
| Viscosity: | 1 770 ± 370 mPa.s @ 25°C |

| , | <u> </u> |
|--------------------|------------|
| Solubility | |
| Water solubility : | Insoluble. |
| Fat solubility : | Not stated |

| Water solubility : | Insoluble. |
|---|-------------|
| Fat solubility: | Not stated. |
| Partition coefficient n-octanol/water (log value) | |

| · - / | |
|---|---------------|
| Partition coefficient: n-octanol/water: | Not stated. |
| Vapour pressure | |
| Vapour pressure (50°C) : | Not relevant. |
| Density and/or relative density | |

| Vapour pressure (50°C): | Not relevant. |
|---------------------------------|--------------------|
| Density and/or relative density | |
| Density: | 1.16 ± 0.02 @ 20°C |

Relative vapour density

| Vapour density : | Not stated. |
|------------------------|-------------|
| 9.2. Other information | |

Index of refraction: 1.5560 ± 0.002 @ 25 °C

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

May cause an allergic reaction by skin contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and a respiratory tract sensitiser as well as an irritant.

Constituents with a low molecular weight irritate the eyes, mucous membranes and the skin

Repeated contact with the skin may cause irritation and hypersensitisation, possibly in combination with other epoxide compounds.

11.1.1. Substances

Acute toxicity:

BUTANEDIOLDIGLYCIDYL ETHER (CAS: 2425-79-8)

Oral route: LD50 = 1134 mg/kg

Species: Rat

Dermal route : LD50 = 1130 mg/kg

Species: Rabbit

Inhalation route (Vapours): LC50 = 10 mg/l

Duration of exposure: 4 h

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Oral route : LD50 = 11400 mg/kg

Species : Rat

Dermal route: LD50 = 2000 mg/kg

Species : Rat

Skin corrosion/skin irritation :

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

SR GREENPOXY 33 - 2052

Species: Rabbit

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

11.1.2. Mixture

Respiratory or skin sensitisation:

Contains epoxy compounds. May cause an allergic reaction.

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer):

CAS 1675-54-3: IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12: ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

BUTANEDIOLDIGLYCIDYL ETHER (CAS: 2425-79-8)

Fish toxicity: LC50 = 13 mg/l

Species : Oryzias latipes Duration of exposure : 96 h

Crustacean toxicity: EC50 = 223 mg/l

Species : Daphnia magna Duration of exposure : 48 h

Aquatic plant toxicity: ECr50 > 93 mg/l

Species: Others

Duration of exposure: 72 h

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Fish toxicity: LC50 = 1.3 mg/l

Duration of exposure: 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity: EC50 = 2.1 mg/l

Species : Daphnia sp. Duration of exposure : 48 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

NOEC = 0.3 mg/l Species : Daphnia magna Duration of exposure : 21 days

OECD Guideline 211 (Daphnia magna Reproduction Test)

Algae toxicity: ECr50 > 11 mg/l

Duration of exposure: 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

BUTANEDIOLDIGLYCIDYL ETHER (CAS: 2425-79-8)

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

SR GREENPOXY 33 - 2052

BUTANEDIOLDIGLYCIDYL ETHER (CAS: 2425-79-8)

Octanol/water partition coefficient : log Koe = 0.01

Bioaccumulation: BCF = 3.162

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Octanol/water partition coefficient : log Koe <= 3.78

Bioaccumulation: BCF < 100.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws):

WGK 2: Hazardous for water.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste):

07 01 08 * other still bottoms and reaction residues

SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

14.1. UN number or ID number

3082

14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane, butanedioldiglycidyl ether)

14.3. Transport hazard class(es)

- Classification :



9

14.4. Packing group

Ш

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

| ADR/RID | Class | Code | Pack gr. | Label | Ident. | LQ | Provis. | EQ | Cat. | Tunnel |
|---------|-------|------|----------|-------|--------|-----|---------|----|------|--------|
| | 9 | M6 | III | 9 | 90 | 5 L | 274 335 | E1 | 3 | - |
| | | | | | | | 375 601 | | | |

*Not subject to this regulation if Q \leq 5 I / 5 kg (ADR 3.3.1 - DS 375)

| IMDG | Class | 2°Label | Pack gr. | LQ | EMS | Provis. | EQ | Stowage | Segregati |
|------|-------|---------|----------|-----|----------|---------|----|----------|-----------|
| | | | | | | | | Handling | on |
| | 9 | - | III | 5 L | F-A. S-F | 274 335 | E1 | Category | - |
| | | | | | | 969 | | Α | |

*Not subject to this regulation if Q <= 5 I / 5 kg (IMDG 3.3.1 - 2.10.2.7)

| IATA | Class | 2°Label | Pack gr. | Passager | Passager | Cargo | Cargo | note | EQ |
|------|-------|---------|----------|----------|----------|-------|-------|-----------|----|
| | 9 | - | III | 964 | 450 L | 964 | 450 L | A97 A158 | E1 |
| | | | | | | | | A197 A215 | |
| | 9 | - | III | Y964 | 30 kg G | - | - | A97 A158 | E1 |
| | | | | | | | | A197 A215 | |

^{*}Not subject to this regulation if Q \leq 5 I / 5 kg (IATA 4.4.4 - DS A197)

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane)

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2019/521 (ATP 12)
- Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2: Hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

| <u> </u> | |
|----------|--|
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H411 | Toxic to aquatic life with long lasting effects. |

Abbreviations:

 $\ensuremath{\mathsf{LD50}}$: The dose of a test substance resulting in 50% lethality in a given time period.

LC50: The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC: The concentration with no observed effect.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE: Acute Toxicity Estimate

BW : Body Weight

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

UFI: Unique formulation identifier.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS05 : Corrosion GHS07 : Exclamation mark GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.