



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : SG 715 BLANC
Product code : 926.
EPOXY RESIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Epoxy resin
Uses advised against : data not available

1.3. Details of the supplier of the safety data sheet

Registered company name : SICOMIN Composites.
Address : 31 avenue de la Lardiere - BP 23.13161.Chateauneuf les Martigues.France.
Telephone : +33 (0)4 42 42 30 20. Fax : +33 (0)4 42 81 29 29.
e-mail: composites@sicomin.com
Site web : <http://www.sicomin.com>

1.4. Emergency telephone number : .

Association/Organisation : INRS / ORFILA tél: +33(0)1.45.42.59.59 - (FRANCE) .

Other emergency numbers

Health and Safety Executive (HSE) Chemicals Regulation Directorate - Telephone: +44 151 951 3317 - USA : +1/ 800/ 424.9300

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1C (Skin Corr. 1C, H314).
Serious eye damage, Category 1 (Eye Dam. 1, H318).
Skin sensitisation, Category 1 (Skin Sens. 1, H317).
Reproductive toxicity, Category 1B (Repr. 1B, H360).
Specific target organ toxicity (repeated exposure), Category 2 (STOT RE 2, H373).
Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

GHS09

GHS07

GHS08

Signal Word :

DANGER

Product identifiers :

EC 216-823-5	2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE
EC 500-006-8	FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL
EC 238-878-4	QUARTZ
EC 608-489-8	TRIMETHYLOLPROPANE TRIGLYCIDYLETHER
603-103-00-4	OXIRANE, MONO[(C 12-14-ALKYLOXY)METHYL] DERIVS.
EC 249-237-3	METHYL TOLUENESULFONATE

Additional labeling :

EUH205 Contains epoxy constituents. May produce an allergic reaction.
For professional use only.

Hazard statements :

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H360F May damage fertility.
H373 May cause damage to organs through prolonged or repeated exposure .
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P202 Do not handle until all safety precautions have been read and understood.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 1675-54-3 EC: 216-823-5 REACH: 01-2119456619-26-XXXX 2,2'-[1-(METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411		25 \leq x % < 50
CAS: 9003-36-5 EC: 500-006-8 REACH: 01-2119454392-40-XXXX FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411		10 \leq x % < 25
CAS: 14808-60-7 EC: 238-878-4 REACH: N.A (Annexe V.7) QUARTZ	GHS08 Wng STOT RE 2, H373	[1]	10 \leq x % < 25
CAS: 30499-70-8 EC: 608-489-8 TRIMETHYLOLPROPANE TRIGLYCIDYLETHER	GHS05, GHS09, GHS07, GHS08 Dgr Skin Corr. 1C, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Repr. 1B, H360F Aquatic Chronic 2, H411	[2]	2.5 \leq x % < 10
INDEX: 603-103-00-4 CAS: 68609-97-2 EC: 271-846-8 REACH: 01-2119485289-22-XXXX OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS.	GHS07 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317		2.5 \leq x % < 10

CAS: 28804-47-9 EC: 249-237-3 REACH: 02-2114675466-36-XXXX METHYL TOLUENESULFONATE	GHS06 Dgr Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319	1 <= x % < 2.5
---	---	----------------

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

If breathing is irregular or stopped, that qualified personnel provide artificial respiration and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor :

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to remain under medical supervision for 48 hours.

Contact a specialist for treatment poisoning if large quantities have been ingested or inhaled.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- powder

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode.
Wear conform with the European standard EN 469.

SECTION 6 : ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

Avoid exposure to pregnant women and warn women of child-bearing age of the possible risks

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid exposure - obtain special instructions before use.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Store in original container protected from direct sunlight in a dry, cool and well ventilated area away from heat sources.

Keep container tightly closed in a dry place.

Store away from heat and cold.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

Suggested application : Epoxy tooling gelcoat

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
14808-60-7	0.05 mg/m3	-	-	-	R

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
14808-60-7	-	0.1 A	-	-	-	25

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
14808-60-7	0.3 mg/m3	-	-	-	R

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Final use:	Workers.
Exposure method:	Dermal contact.
Potential health effects:	Short term local effects.
DNEL :	8.3 µg de substance/cm2
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	104.15 mg/kg de poids corporel/jour
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	29.39 mg de substance/m3
Final use:	Man exposed via the environment.
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	6.25 mg/kg de poids corporel/jour
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	62.5 mg/kg de poids corporel/jour
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	8.7 mg de substance/m3

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Final use:	Workers.
Exposure method:	Dermal contact.
Potential health effects:	Short term systemic effects.
DNEL :	8.3 mg/kg de poids corporel/jour
Exposure method:	Dermal contact.
Potential health effects:	Long term systemic effects.
DNEL :	8.3 mg/kg de poids corporel/jour
Exposure method:	Inhalation.
Potential health effects:	Short term systemic effects.
DNEL :	12.3 mg de substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	12.3 mg de substance/m3
Final use:	Man exposed via the environment.
Exposure method:	Ingestion.
Potential health effects:	Short term systemic effects.
DNEL :	0.75 mg/kg de poids corporel/jour
Exposure method:	Ingestion.
Potential health effects:	Long term systemic effects.
DNEL :	0.75 mg/kg de poids corporel/jour
Exposure method:	Dermal contact.
Potential health effects:	Short term systemic effects.
DNEL :	3.6 mg/kg de poids corporel/jour
Exposure method:	Dermal contact.

Potential health effects:	Long term systemic effects.
DNEL :	3.6 mg/kg de poids corporel/jour
Exposure method:	Inhalation.
Potential health effects:	Short term systemic effects.
DNEL :	0.75 mg de substance/m3
Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	0.75 mg de substance/m3

Predicted no effect concentration (PNEC):

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Environmental compartment:	Soil.
PNEC :	0.237 mg/kg
Environmental compartment:	Fresh water.
PNEC :	0.003 mg/l
Environmental compartment:	Sea water.
PNEC :	0.0003 mg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.0254 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.294 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.0294 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	10 mg/l

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Environmental compartment:	Soil.
PNEC :	0.05 mg/kg
Environmental compartment:	Fresh water.
PNEC :	3 µg/l
Environmental compartment:	Sea water.
PNEC :	0.3 µg/l
Environmental compartment:	Intermittent waste water.
PNEC :	0.013 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.5 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.5 mg/kg
Environmental compartment:	Waste water treatment plant.
PNEC :	10 mg/l

8.2. Exposure controls

Use only with adequate ventilation or provided with ventilation at the source.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

Mask with filter type A, B, E, K, P

Attention! If the protection group is insufficient.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Viscous liquid.
Aspect :	Gel coat
Color:	white

Important health, safety and environmental information

pH :	Not relevant.
Boiling point/boiling range :	Not relevant.
Flash Point Interval :	FP > 100°C.
Vapour pressure (50°C) :	Not relevant.
Density :	1.16 ± 0.01 @ 20 °C
Water solubility :	Insoluble.
Viscosity :	24 350 ± 4 850 mPa.s @ 25 °C
Melting point/melting range :	Not relevant.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not relevant.

9.2. Other information

Miscibility

Alcohols, aromatic hydrocarbons

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between one and four hours.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

May cause an allergic reaction by skin contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and a respiratory tract sensitiser as well as an irritant.

Constituents with a low molecular weight irritate the eyes, mucous membranes and the skin

Repeated contact with the skin may cause irritation and hypersensitisation, possibly in combination with other epoxide compounds.

Presumed human reproductive toxicant.

May damage fertility.

May cause severe damage to organs in the event of repeated or prolonged exposure.

11.1.1. Substances**Acute toxicity :**

METHYL TOLUENESULFONATE (CAS: 28804-47-9)

Oral route : LD50 = 341 mg/kg
Species : Rat

QUARTZ (CAS: 14808-60-7)

Oral route : LD50 > 2000 mg/kg
Species : Rat

Dermal route : LD50 > 2000 mg/kg

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Oral route : LD50 > 2000 mg/kg
Species : Rat

Dermal route : LD50 > 2000 mg/kg
Species : Rabbit

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Oral route : LD50 = 11400 mg/kg
Species : Rat

Dermal route : LD50 = 2000 mg/kg
Species : Rat

Skin corrosion/skin irritation :

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Species : Rabbit

OCDE Ligne directrice 404 (Effet irritant/corrosif aigu sur la peau.)

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Species : Rabbit

OCDE Ligne directrice 404 (Effet irritant/corrosif aigu sur la peau.)

Serious damage to eyes/eye irritation :

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Conjunctival redness :

Average score = 0

Species : Rabbit

Conjunctival oedema :

Average score = 0

Species : Rabbit

OCDE Ligne directrice 405 (Effet irritant/corrosif aigu sur les yeux)

Germ cell mutagenicity :

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Mutagenesis (in vitro) :

Positive.

Ames test (in vitro) :

Positive.

Reproductive toxicant :

TRIMETHYLOLPROPANE TRIGLYCIDYLETHER (CAS: 30499-70-8)

May damage fertility.

11.1.2. Mixture**Respiratory or skin sensitisation :**

Contains epoxy compounds. May cause an allergic reaction.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 1675-54-3 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 14808-60-7 : IARC Group 1 : The agent is carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity**12.1.1. Substances**

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Fish toxicity :

LC50 = 1.3 mg/l

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 2.1 mg/l

Species : Daphnia sp.

Duration of exposure : 48 h

OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity :

ECr50 > 11 mg/l

Duration of exposure : 72 h

METHYL TOLUENESULFONATE (CAS: 28804-47-9)

Fish toxicity :

LC50 >= 4.6 mg/l

Species : Leuciscus idus

Duration of exposure : 96 h

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Fish toxicity :

LC50 = 2.54 mg/l

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 2.55 mg/l

Species : Daphnia sp.
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity :
ECr50 > 1000 mg/l
Species : Selenastrum capricornutum
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

METHYL TOLUENESULFONATE (CAS: 28804-47-9)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Biodegradability : Non-rapidly degradable.

2,2'-[[1-METHYLETHYLIDENE]BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL (CAS: 9003-36-5)

Octanol/water partition coefficient : log K_{ow} = 3.3

Bioaccumulation : BCF = 150

2,2'-[[1-METHYLETHYLIDENE]BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE (CAS: 1675-54-3)

Octanol/water partition coefficient : log K_{ow} = 4

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

3082

14.2. UN proper shipping name

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane, formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

14.3. Transport hazard class(es)

- Classification :



9

14.4. Packing group

III

14.5. Environmental hazards

- Environmentally hazardous material :

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M6	III	9	90	5 L	274 335 375 601	E1	3	-

*Not subject to this regulation if Q <= 5 l / 5 kg (ADR 3.3.1 - DS 375)

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	9	-	III	5 L	F-A,S-F	274 335 969	E1

*Not subject to this regulation if Q <= 5 l / 5 kg (IMDG 3.3.1 - 2.10.2.7)

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	9	-	III	964	450 L	964	450 L	A97 A158 A197	E1
	9	-	III	Y964	30 kg G	-	-	A97 A158 A197	E1

*Not subject to this regulation if Q <= 5 l / 5 kg (IATA 4.4.4 - DS A197)

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2017/776 (ATP 10)

- Container information:

No data available.

Usage restrictions apply to the product : See annex XVII of EC regulation No. 1907/2006.

For professional users only.

- Particular provisions :


No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=3 Inflammability=3 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure .
H411	Toxic to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungskategorie (Water Hazard Class).

GHS05 : Corrosion

GHS07 : Exclamation mark

GHS08 : Health hazard

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.