Version: N°1 (26/02/2016) SICOMIN Composites

SILICELL - 315



Date: 26/02/2016 Page 1/7

Revision: N°4 (26/02/2016)

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: SILICELL Product code: 315.

FILLER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Glue, silicone rubber, paints and lacquers, sealing masses ..

1.3. Details of the supplier of the safety data sheet

Registered company name: SICOMIN Composites.

Address: 31 avenue de la Lardiere - BP 23.13161. Chateauneuf les Martigues. France.

Telephone: +33 (0)4 42 42 30 20. Fax: +33 (0)4 42 81 29 29.

e-mail: composites@sicomin.com Site web : http://www.sicomin.com 1.4. Emergency telephone number : .

Association/Organisation: ORFILA tél: +33(0)1.45.42.59.59.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

No labelling requirements for this mixture.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Identification	(EC) 1272/2008	Note	%
CAS: 7631-86-9		[1]	50 <= x % < 100
EC: 231-545-4			
REACH: 01-2119379499-16-XXXX			
SILICIUM OXYDE			

Information on ingredients:

[1] Substance for which maximum workplace exposure limits are available.

Version : N°1 (26/02/2016) SICOMIN Composites

SILICELL - 315

Date: 26/02/2016 Page 2/7

Revision: N°4 (26/02/2016)

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation:

If inhaled, move the patient to fresh air and keep warm and rest.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

Flush with large amounts of water. Remove contact lenses if the victim is. Continue to rinse. Seek medical attention if symptoms persist.

In the event of splashes or contact with skin:

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

Wash skin thoroughly with soap and water or use a cleanser.

In the event of swallowing:

Seek medical attention, showing the label.

Rinse mouth and drink plenty. If symptoms persist, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: cough, sneezing

4.3. Indication of any immediate medical attention and special treatment needed

Information for the doctor:

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed personmay need to remain under medical supervision for 48 hours.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- carbon dioxide (CO2)
- powder

Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Firefighters should wear suitable protective clothing and a respirator mask with self- full operated in positive pressure mode. Wear conform with the European standard EN 469.

Version : N°1 (26/02/2016) SICOMIN Composites

SILICELL - 315

Date: 26/02/2016 Page 3/7

Revision: N°4 (26/02/2016)

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Retrieve the product by mechanical means (sweeping/vacuuming): do not generate dust.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Fire prevention:

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep container tightly closed in a dry place.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS VME: VME: Excess Notes 7631-86-9 - 4 mg/m3 E - DFG, 2, Y

8.2. Exposure controls

Use only with adequate ventilation or provided with ventilation at the source.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):





Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Version : N°1 (26/02/2016) SICOMIN Composites

SILICELL - 315

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

Date: 26/02/2016 Page 4/7

Revision: N°4 (26/02/2016)

- Eye / face protection

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended:

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing dust.

Particle filter according to standard EN143:

- P2 (White)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information:

Physical state: Powder or dust.

Color: white Aspect: powder

Important health, safety and environmental information

pH (aqueous solution):

pH:

Not relevant.

Boiling point/boiling range:

Not relevant.

Flash point interval:

Not relevant.

Vapour pressure (50°C):

Not relevant.

Not relevant.

Density:

2.2 g/cm3 @ 20°C

Water solubility:

Soluble. > 1mg/l

Melting point/melting range:

Melting point/melting range : 1700 °C.

Self-ignition temperature : Not relevant.

Decomposition point/decomposition range : Not relevant.

% VOC: 0

9.2. Other information

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid:

- formation of dusts

Dusts can form an explosive mixture with air.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version : N°1 (26/02/2016) SICOMIN Composites

SILICELL - 315

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Acute toxicity:

SILICIUM OXYDE (CAS: 7631-86-9)

Oral route : LD50 > 3300.0 mg/kg

Species: Rat

OECD Guideline 401 (Acute Oral Toxicity)

Date: 26/02/2016 Page 5/7

Revision: N°4 (26/02/2016)

Dermal route : LD50 > 5000 mg/kg

Species: Rabbit

Inhalation route (Dusts/mist): LC50 = 0.139 mg/l

Species: Rat

11.1.2. Mixture

Acute toxicity:

LD50 > 3300 mg/kg Species : Rabbit LD50 > 5000 mg/kg Species : Rat

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

SILICIUM OXYDE (CAS: 7631-86-9)

Fish toxicity: LC50 > 10000 mg/l

Species : Brachydanio rerio Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity: EC50 > 1000 mg/l

Species : Daphnia magna Duration of exposure : 24 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

12.1.2. Mixtures

LC50 > 10000 mg/l

Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)

EC50 > 1000 mg/l

Duration of exposure: 24 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version : N°1 (26/02/2016) SICOMIN Composites

SILICELL - 315

12.2. Persistence and degradability

12.2.1. Substances

SILICIUM OXYDE (CAS: 7631-86-9)

Biodegradability:

no degradability data is available, the substance is considered as not degrading quickly.

no degradability data is available, the substance is considered as not degrading quickly.

Date: 26/02/2016 Page 6/7

Revision: N°4 (26/02/2016)

12.2.2. Mixtures

Biodegradability:

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK):

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14: TRANSPORT INFORMATION

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
 EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

- Container information:

No data available.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version : N°1 (26/02/2016) SICOMIN Composites

SILICELL - 315

Date: 26/02/2016 Page 7/7

Revision: N°4 (26/02/2016)

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws): Hazardous for water.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704):

NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Abbreviations:

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods. IATA : International Air Transport Association.

ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

 $WGK: Wasserge fahrdungsklasse \ (Water\ Hazard\ Class).$

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.